

# Lasttabel t.b.v. hijsbanden en rondstropen

kleurcode EN 1492-1 & EN 1492-2	max. veilige werklust met 1 hijsband of rondstrop							max. veilige werklust met 2 hijsbanden of rondstropen			
	enkel direct	enkel gestropt	buitenhoek					buitenhoek			
			tot 7°	7° - 45°	45° - 60°	7° - 45°	45° - 60°	direct tot 45°	direct 45° - 60°	gestropt tot 45°	gestropt 45° - 60°
faktor	1	0,8	2	1,4	1	0,7	0,5	1,4	1,12	1	0,8
WLL 1t	1,00t	800 kg	2,00t	1,40t	1,00t	700 kg	500 kg	1,40t	1,12t	1,00t	800 kg
WLL 2t	2,00t	1,60t	4,00t	2,80t	2,00t	1,40t	1,00t	2,80t	2,24t	2,00t	1,60 t
WLL 3t	3,00t	2,40t	6,00t	4,20t	3,00t	2,10t	1,50t	4,20t	3,36t	3,00t	2,40 t
WLL 4t	4,00t	3,20t	8,00t	5,60t	4,00t	2,80t	2,00t	5,60t	4,48t	4,00t	3,20 t
WLL 5t	5,00t	4,00t	10,00t	7,00t	5,00t	3,50t	2,50t	7,00t	5,60t	5,00t	4,00 t
WLL 6t	6,00t	4,80t	12,00t	8,40t	6,00t	4,20t	3,00t	8,40t	6,72t	6,00t	4,80 t
WLL 8t	8,00t	6,40t	16,00t	11,20t	8,00t	5,60t	4,00t	11,20t	8,96t	8,00t	6,40 t
WLL 10 t	10,00t	8,00t	20,00t	14,00t	10,00t	7,00t	5,00t	14,00t	11,20t	10,00t	8,00 t
WLL 12t	12,00t	9,60t	24,00t	16,80t	12,00t	8,40t	6,00t	16,80t	13,44t	12,00t	9,60 t
WLL 15t	15,00t	12,00t	30,00t	21,00t	15,00t	10,50t	7,50t	21,00t	16,80t	15,00t	12,00 t
WLL 20t	20,00t	16,00t	40,00t	28,00t	20,00t	14,00t	10,00t	28,00t	22,40t	20,00t	16,00 t
WLL 25t	25,00t	20,00t	50,00t	35,00t	25,00t	17,50t	12,50t	35,00t	28,00t	25,00t	20,00 t
WLL 30t	30,00t	24,00t	60,00t	42,00t	30,00t	21,00t	15,00t	42,00t	33,60t	30,00t	24,00 t
WLL 40t	40,00t	32,00t	80,00t	56,00t	40,00t	28,00t	20,00t	56,00t	44,80t	40,00t	32,00 t
WLL 50t	50,00t	40,00t	100,00t	70,00t	50,00t	35,00t	25,00t	70,00t	56,00t	50,00t	40,00 t
WLL 60t	60,00t	48,00t	120,00t	84,00t	60,00t	42,00t	30,00t	84,00t	67,20t	60,00t	48,00 t
WLL 70t	70,00t	56,00t	140,00t	98,00t	70,00t	49,00t	35,00t	98,00t	78,40t	70,00t	56,00 t
WLL 80t	80,00t	64,00t	160,00t	112,00t	80,00t	56,00t	40,00t	112,00t	89,60t	80,00t	64,00 t
WLL 100t	100,00t	80,00t	200,00t	140,00t	100,00t	70,00t	50,00t	140,00t	112,00t	100,00t	80,00 t